



Switching    WiFi    Camera Security    Door Access    Cloud Keys & Gateways    Power Tech    New I

Camera Security > [AI Theta Pro](#)

Datasheet

In The Box	Marketing Images	Installation Guide
------------	------------------	--------------------



## Mechanical

<b>Dimensions</b>	UVC-AI-Theta-Hub: 140 x 70 x 38 mm (5.5 x 2.8 x 1.5") UVC-AI-Theta-ProLens360: Ø36.6 x 58.9 mm (Ø1.4 x 2.3") UVC-AI-Theta-ProLens360 Flush Mount: Ø54.6 x 60.4 mm (Ø2.2 x 2.4")
<b>Weight</b>	UVC-AI-Theta-Hub: 330 g (11.6 oz) UVC-AI-Theta-Hub Mount: 35 g (1.2 oz) UVC-AI-Theta-ProLens360: 58 g (2 oz) UVC-AI-Theta-ProLens360 Flush Mount: 24 g (0.8 oz)
<b>Enclosure material</b>	UVC-AI-Theta-Hub: aluminum alloy UVC-AI-Theta-ProLens360: aluminum alloy, polycarbonate
<b>Mount material</b>	UVC-AI-Theta-Hub: aluminum alloy UVC-AI-Theta-ProLens360 Flush Mount: polycarbonate
<b>Cable jacket enclosure dimensions</b>	28 x 13 x 7.5 mm (1.1 x 0.5 x 0.3")
<b>Cable jacket enclosure material</b>	PVC
<b>Cable length</b>	1 m (3.3 ft)
<b>Cable diameter</b>	3.7 mm (0.15")
<b>Cable jacket material</b>	Woven fabric
<b>Cable weight</b>	18 g (0.63 oz)
<b>Cable connector type</b>	Theta proprietary

---

## Optics

<b>Sensor</b>	8MP 1/1.8" CMOS
<b>Lens</b>	Fixed focal length
<b>View angle</b>	H: 180°, V: 180°, D: 180°

---

## Video

<b>Resolution</b>	4MP 2160 x 2160 (1:1)
<b>Max. frame rate</b>	24 FPS
<b>Image settings</b>	Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay
<b>Power supply</b>	5V DC, 0.5A

---

## System

<b>Processor</b>	Quad-core Arm® Cortex®-A53 based chip
<b>Networking interface</b>	GbE RJ45 port
<b>Max. power consumption</b>	12.5W
<b>Power method</b>	PoE
<b>Supported voltage range</b>	37—57V DC
<b>Output power</b>	5V DC, 1A per port
<b>Display</b>	0.96" color display
<b>Button</b>	Factory reset
<b>Mounting</b>	Wall, ceiling mount
<b>Ambient operating temperature</b>	-20 to 40° C (-4 to 104° F)
<b>Ambient operating humidity</b>	10 to 90% noncondensing
<b>Certifications</b>	FCC, IC, CE

---

## Audio

<b>Microphone</b>	Supports optional AI Theta Audio module for two-way audio (sold separately)
<b>Speaker</b>	Supports optional AI Theta Audio module for two-way audio (Sold separately)

---

## Software

<b>UniFi OS application</b>	UniFi Protect
<b>Mobile app</b>	UniFi Protect iOS™ and Android™

### Stay in Touch



[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.