


MAXHUB Commercial Display CMA-T Series

Taking simplicity, safety and flexibility to new levels. MAXHUB Commercial Display makes every organization more effective and productive.




Professional 4K Display

4K Resolution, 800 nits brightness
Anti-Glare, 25% Haze



Wireless Screen Sharing

Share your screen through MAXHUB
Share app or wireless dongle




External Control

Display control through IP
or RS232 protocol




Device Management

Manage through cloud based
MAXHUB Pivot




Built-in Speakers

2 x 16W Dual speakers



Upgrade Your Display

OPS slot availability to transform your
display into a windows-based display



24/7 Operation

Reliable and continuous
display performance



Energy Saving

ErP Certified
Energy Star 8.0 Certified

Display			
Screen Size (class)	55"	65"	75"
Diagonal	54.6" 138.7cm	64.5" 163.9cm	74.5" 189.3cm
Panel Type	VA	VA	VA
Haze	25% (Anti-Glare)	25% (Anti-Glare)	25% (Anti-Glare)
Aspect Ratio	16:9	16:9	16:9
Native Resolution	3840 × 2160	3840 × 2160	3840 × 2160
Refresh Rate	60Hz	60Hz	60Hz
Brightness (Typ.)	800 nits	800 nits	800 nits
Backlight Type	DLED	DLED	DLED
Contrast Ratio	6,000:1 (Typ) 1,000,000:1 (Dynamic)	6,000:1 (Typ) 1,000,000:1 (Dynamic)	6,000:1 (Typ) 1,000,000:1 (Dynamic)
Viewing Angle (H × V)	178°	178°	178°
Response Time	6.5ms	6.5ms	6.5ms
Life Time (Min.)	50,000 hours	50,000 hours	50,000 hours
Operation Hours (Hours / Day)	24 / 7	24 / 7	24 / 7
Orientation	Portrait / Landscape	Portrait / Landscape	Portrait / Landscape

Internal Player			
Processor	A55 × 4	A55 × 4	A55 × 4
Graphic	Mali-G52 × 2	Mali-G52 × 2	Mali-G52 × 2
Memory	4G	4G	4G
Storage	32G	32G	32G
Operating System	MAXHUB Signage OS	MAXHUB Signage OS	MAXHUB Signage OS
UI Resolution	4K	4K	4K

Connectivity			
Input	HDMI IN 2.1 × 2 USB Type-C × 1 (PD 65W) USB Type-A 3.0 × 1 USB Type-A 2.0 × 1 RJ45 IN × 1	HDMI IN 2.1 × 3 USB Type-C × 1 (PD 65W, BYOD) USB Type-A 3.0 × 1 USB Type-A 2.0 × 1 RJ45 IN × 1	HDMI IN 2.1 × 3 USB Type-C × 1 (PD 65W, BYOD) USB Type-A 3.0 × 1 USB Type-A 2.0 × 1 RJ45 IN × 1
Output	HDMI OUT 2.0 × 1 SPDIF × 1 (Optical) AUDIO OUT × 1 (3.5mini jack)	HDMI OUT 2.0 × 1 SPDIF × 1 (Optical) RJ45 OUT × 1 AUDIO OUT × 1 (3.5mini jack)	HDMI OUT 2.0 × 1 SPDIF × 1 (Optical) RJ45 OUT × 1 AUDIO OUT × 1 (3.5mini jack)
External Control	RS232 × 1 / IR Receiver	RS232 × 1 / IR Receiver	RS232 × 1 / IR Receiver
Wi-Fi	Removable Wi-Fi Module Wi-Fi 6 Support 2.4GHz & 5GHz 802.11ac/b/g/n/a/ax	Removable Wi-Fi Module Wi-Fi 6 Support 2.4GHz & 5GHz 802.11ac/b/g/n/a/ax	Removable Wi-Fi Module Wi-Fi 6 Support 2.4GHz & 5GHz 802.11ac/b/g/n/a/ax
OPS Slot	No	Yes, 80pin	Yes, 80pin

Mechanical Specification			
Bezel Width (L × R × T × B)	9.9 / 9.9 / 9.9 / 9.9 mm 0.39 / 0.39 / 0.39 / 0.39 inch	15.9 / 15.9 / 15.9 / 15.9 mm 0.63 / 0.63 / 0.63 / 0.63 inch	15.9 / 15.9 / 15.9 / 15.9 mm 0.63 / 0.63 / 0.63 / 0.63 inch
Product Dimension (W × H × D)	1233 × 703.5 × 71.4 mm 48.54 × 27.7 × 2.81 inch	1463.3 × 838.3 × 76.4 mm 57.61 × 33.0 × 3.0 inch	1685.6 × 963.7 × 81.6 mm 66.36 × 37.94 × 3.21 inch
Package Dimension (W × H × D)	1332 × 819 × 156 mm 52.44 × 32.24 × 6.14 inch	1628 × 942 × 208 mm 64.09 × 37.09 × 8.19 inch	1863 × 1090 × 225 mm 73.35 × 42.91 × 8.86 inch
Product Weight (Net)	13.40 kg / 29.54 pounds	25.40 kg / 56.0 pounds	34.65 kg / 76.40 pounds
Package Weight (Gross)	19.5 kg / 43 pounds	33.25 kg / 73.30 pounds	48.15 kg / 106.15 pounds
VESA Mount (mm)	400 × 200	600 × 400	800 × 600
Handle	No	Yes	Yes

Environmental Conditions

Operation Temperature	0°C ~ 40°C	0°C ~ 40°C	0°C ~ 40°C
Operation Humidity	10% ~ 90%RH	10% ~ 90%RH	10% ~ 90%RH
Storage Temperature	-20°C ~ 60°C	-20°C ~ 60°C	-20°C ~ 60°C
Storage Humidity	10% ~ 90%RH	10% ~ 90%RH	10% ~ 90%RH

Power

Power Supply	100-240V-50/60Hz	100-240V-50/60Hz	100-240V-50/60Hz
Power Consumption (Standby mode)	0.5W	0.5W	0.5W
Power Consumption (Typical)	121.5W	158.4W	190.5W

Sound

Speaker Power (Max.)	2 × 16W	2 × 16W	2 × 16W
----------------------	---------	---------	---------

Certification

Safety	IEC 62368-1	IEC 62368-1	IEC 62368-1
EMC	Class B	Class B	Class B
ErP	Yes	Yes	Yes
Energy Star	Yes	Yes	Yes

Feature

Built-In Media Player	Yes	Yes	Yes
Device Management System	MAXHUB Pivot	MAXHUB Pivot	MAXHUB Pivot
Screen Share	MAXHUB Share / BYOM	MAXHUB Share / BYOM	MAXHUB Share / BYOM

Accessory

Included in the package	Power Cord × 1 HDMI Cable × 1 Wi-Fi Module × 1 Remote Control × 1 Wall Mount × 1	Power Cord × 1 HDMI Cable × 1 Wi-Fi Module × 1 Remote Control × 1 Wall Mount × 1	Power Cord × 1 HDMI Cable × 1 Wi-Fi Module × 1 Remote Control × 1 Wall Mount × 1
-------------------------	--	--	--

Optional



OPS (OPS62A)



Wireless Dongle (WT13)



Mobile Stand (ST41B)



Mobile Stand (ST23C)

Warranty

Display	3 years warranty	3 years warranty	3 years warranty
---------	------------------	------------------	------------------



MAXHUB
Beyond Collaboration

