
Hardware

Processor	Quad-core ARM® Cortex®-A53 at 1.5 GHz
System memory	4 GB DDR4
On-board storage	512 GB NVMe SSD
Management interface	Ethernet Bluetooth
Networking interface	LAN: (4) 1/2.5 GbE RJ45 ports WAN: (1) 1/2.5 GbE RJ45 port
IDS/IPS throughput	1.5 Gbps* *Measured with iPerf3 on a DHCP network. Performance may be reduced with PPPoE depending on ISP implementation.
Power method	USB type C (5V DC/5A)
Supported voltage range	100-240V AC
Max. power consumption	16.1W
LCM display	0.96" status display
Button	Factory reset
Ambient operating temperature	-10 to 40° C (14 to 104° F)
Ambient operating humidity	5 to 95% noncondensing
Certifications	CE, FCC, IC

Gateway Features

Performance	Redundant WAN with failover and load balancing WiFi QoS with UniFi APs Application, domain, and country-based QoS Application and device type identification Additional internet failover with LTE Backup Internet quality and outage reporting
Next-generation security	Application-aware firewall rules Signature-based IPS/IDS threat detection Content, country, domain, and ad filtering

VLAN/subnet-based traffic segmentation
Full stateful firewall

Advanced networking

License-free SD-WAN
WireGuard, L2TP and OpenVPN server
OpenVPN client
OpenVPN and IPsec site-to-site VPN
One-click Teleport and Identity VPN
Policy-based WAN and VPN routing
DHCP relay
Customizable DHCP server
IGMP proxy
IPv6 ISP support

LEDs

Ethernet

Green: link/activity

Application Requirements

Mobile app

UniFi iOS™ and Android™: Version 10.17.2 and later

Stay in Touch



[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.