

MAXHUB Commercial Display CMD Series

Model: ND65CMD, ND75CMD

Experience seamless collaboration with the MAXHUB CMD series commercial display. With MAXHUB BYOM functionality, you can easily connect and share content from your own device. MAXHUB CMD series simplifies meetings by providing a seamless integration of all essential collaboration tools and enhancing productivity.



UHD Professional Display

4K Resolution, High contrast



Audio&Video Module

Optional module, 48M Camera, 8-array Mic




Built-in Speakers

2 × 10W Dual speakers




BYOM Anytime

Embrace drive-free efficiency enabled by MAXHUB BYOM (Bring Your Own Meeting) technology



Powerful Performance

A73 × 4 + A53 × 4 Core, Build-in Android System



Convenient Front Panel

USB Type-C (Full-featured, support 65W Charge for PC) × 1, USB 3.0 × 2



External Control

Optional Display control through IPManage through cloud based or RS232 protocol



IT Management System

Optional Display control through IPManage through cloud based MAXHUB Pivot

Display		
Model	ND65CMD	ND75CMD
Screen Size	65"	75"
Panel Type	VA	VA
Backlight	DLED	DLED
Display Area	1428.48(H) × 803.52(V)mm	1650.24(H) × 928.26(V) mm
Pixel Pitch	0.372 × 0.372mm	0.42975 × 0.42975mm
Resolution	3840(H) × 2160(V)	3840(H) × 2160(V)
Contrast Ratio (Typ.)	6000:1	5000:1
Aspect Ratio	16:9	16:9
Refresh Rate	60Hz	60Hz
Brightness(Typ.)	300 cd/m ²	300 cd/m ²
Operation Hours (Hours / Day)	7 × 16H	7 × 16H
Life Time	≥50000 Hours	≥50000 Hours
Display Color	1.07B (8bit+FRC)	1.07B (8bit+FRC)
Color Gamut(Typ.)	NTSC 72%	NTSC 72%
Viewing Angle (H × V)	178°	178°
Response Time	6.5ms	6.5ms

System		
System	Android 11.0	Android 11.0
CPU	A73 × 4 + A53 × 4	A73 × 4 + A53 × 4
GPU	Mali G52MP8	Mali G52MP8
RAM	4G	4G
ROM	32G	32G

Speaker		
Channel	2.0	2.0
Power	2 × 10W	2 × 10W

Power		
Power Supply	100-240V~50/60Hz	100-240V~50/60Hz
Standby Power Consumption	≤0.5W	≤0.5W
Power Consumption (Typ.)	153W	185W
Power Consumption (Max)	257W	295W

Connectivity		
HDMI IN (2.0)	2	2
USB 2.0	1	1
USB 3.0	2 (Front Panel)	2 (Front Panel)
USB Type-C	1 (PD 65W, Front Panel)	1 (PD 65W, Front Panel)
Touch 2.0	1	1
AUDIO IN	1	1
AUDIO OUT	1	1
RS232	1	1
RJ45 IN	1	1
Wi-Fi	AP + STA Wi-Fi 6 Support 2.4GHz & 5GHz 802.11ac/b/g/n/a/ax	AP + STA Wi-Fi 6 Support 2.4GHz & 5GHz 802.11ac/b/g/n/a/ax
Bluetooth	5.2	5.2

Features		
HDMI CEC	Yes	Yes
RS232/IP Protocol to control	Yes	Yes
Built-In Media Player	Yes	Yes
Device Management System	Yes	Yes
Screen Share	Yes	Yes
Channel memory	Yes	Yes
One-key black screen	Yes	Yes

Accessories		
Included in the package	Power Cord × 1 HDMI Cable (3m) × 1 USB Type-C Cable (1.8m) × 1 Wall Mount × 1 Remote Control × 1 Wireless Module (SI07B) × 1	Power Cord × 1 HDMI Cable (3m) × 1 USB Type-C Cable (1.8m) × 1 Wall Mount × 1 Remote Control × 1 Wireless Module (SI07B) × 1
Optional	Wireless Dongle (WT13) Mobile Stand (ST41B)	Wireless Dongle (WT13) Mobile Stand (ST41B)

Mechanical Specification		
Product Dimension (L×H×D)	1445.7 × 841.3 × 84.9mm	1669 × 968.1 × 75.9mm
Package Dimension (L×W×H)	1610 × 185 × 972mm	1825 × 225 × 1135mm
Thickness of machine and wall mount	116 mm (WIB6540B)	118.9 mm (WIB6540B)
Net Weight	17kg	25kg
Gross Weight	27kg	37kg
VESA	400 × 200mm	400 × 300mm
Wall-hanging Screw Spec	M6 × 30mm	M6 × 30mm

Environmental Conditions		
Operation Temperature	0°C - 40°C	0°C - 40°C
Operation Humidity	10% - 90%RH	10% - 90%RH
Storage Temperature	-20°C - 60°C	-20°C - 60°C
Storage Humidity	10% - 90%RH	10% - 90%RH
Altitude	Below 5000 meters	Below 5000 meters

Certification		Warranty	
Certification	Energy Star	Display	3 years warranty


MAXHUB

Beyond Collaboration

 www.maxhub.com/en/

 sales@maxhub.com

 <https://www.youtube.com/c/MAXHUB>

 <https://www.facebook.com/MAXHUB.Global>

 <https://www.linkedin.com/company/maxhub-overseas/>