



Switching WiFi Camera Security Door Access CloudKeys & Gateways Power Tech New I

Camera Security > [Protect Floodlight](#)

Datasheet

Marketing Images

Installation Guide



## Mechanical

<b>Dimensions</b>	135 x 65 x 50 mm (5.3 x 2.6 x 2")
<b>Weight</b>	Without mount: 216 g (7.6 oz) With flat wall mount: 236 g (8.3 oz) With angle mount: 273 g (9.6 oz)
<b>Enclosure material</b>	Plastic, metal
<b>Mount material</b>	Flat wall mount: plastic Angle mount: plastic
<b>Weatherproofing</b>	IPX5

---

## Hardware

<b>Networking interface</b>	10/100 MbE RJ45 port
<b>Max. power consumption</b>	10.5W
<b>Power method</b>	PoE, 48V DC, 0.22A Max.
<b>ESD/EMP protection</b>	Air: $\pm 8\text{kV}$ , contact: $\pm 8\text{kV}$
<b>RF</b>	Bluetooth 4.0
<b>LEDs</b>	R/B/W
<b>Button</b>	Factory reset
<b>Ambient operating temperature</b>	-10 to 45° C (14 to 113° F)
<b>Ambient operating humidity</b>	20 to 80% noncondensing
<b>Certifications</b>	FCC, IC, CE

---

## Software

<b>Web application</b>	UniFi Protect
<b>Mobile app</b>	UniFi Protect iOS™ and Android™

### Stay in Touch

 

[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.